


## **RFID Reader Product Line**

# ACG HF Mifare Easy Wiegand OEM Module RDHO-0505N0-01

The ACG HF Mifare Easy Wiegand OEM Module is a contact less proximity read/write device that supports various RFID-devices out of the mifare family and the ISO 14443 A standard. The module needs an external application specific antenna to operate. By using the serial interface the device can be connected to a controller or any host system easily. The small form factor enables a design in even into very compact systems. The Wiegand interface is configurable and adoptable to a variety of Wiegand protocols.



### **Typical Applications**

- · e-Payment
- e-Toll Road Pricing
- · e-Ticketing for Events
- e-Ticketing for Public Transport

- Access Control
- PC Access
- Authentication
- Printer / Mobile Devices / Production Equipment

#### **Technical Data**

Part Number	RDHO-0505N0-01		
RF Transmit Frequency	13.56MHz		
Supported Standards	ISO14443A		
Supported Tag-ICs	mifare <sup>®</sup> Standard	SLE66R35	ISO 14443A Tags
	mifare <sup>®</sup> 4k	SLE44R35	
	Serial Number only for:		
	mifare® Pro X		
	mifare <sup>®</sup> Ultralight		
	mifare® DESFire		
Default Configuaration	40bit, Sector 0, Block 0 = Serial Number		
Host Communication	Point-to-Point		
Communications Interface	CMOS-TTL		
Communications Protocol	Wiegand Protocol		
Communications Parameter	30μs Pulswidth		
Firmware Boot-Loader	no		
Software, Driver	Reader Utility for reading / writing Administrator Cards		
Power Supply	5VDC ± 10% regulated		
Current Consumption	90 – 150 mA depending on antenna		
	< 10mA at power down mode		
Reading distance	Up to 85mm, depending on tag and antenna		
RF Transmission Speed	106 kBit/s		
Antenna	External		
Input/Output Connector	Output: 2 status indicator LED lines, 1 Buzzer; Input: invert Read LED / Buzzer function		
Size	(LxWxH) 25.5x30.0x4.8mm ± (L/W) 0.5 (H) 1.0 / 1.00x1.18x0.19Inch ± (L/W) 0.02 (H) 0.04		
Weight	5 g± 10% / 0.01 lb± 10%		
Operating Temperature	-20℃ to +80℃ / -4F to +176F		
Storage Temperature	-40℃ to + 85℃ / -40F to +185F		
Firmware Version	1.0		
MTBF	3.000.000 h		
Approvals/Compliances	RoHS compliant		

#### For more information, please contact the sales office nearest you or visit our website: www.acg-id.com

ACG Identification Technologies GmbH reserves the right to change its services and products at any time without prior notice. ACG provides customer assistance in various technical areas, but does not have full access to data concerning the uses and applications of customer products. Therefore, ACG assumes no responsibility for customer product designs or for infringement of patents and/or the rights of third parties, which may result from assistance provided by ACG.

ACG Identification Technologies GmbH Am Klingenweg 6a D - 65396 Walluf Tel.: +49 (0) 61 23 / 791 - 0 Fax: +49 (0) 61 23 / 791 - 199 RFID@acg-id.com www.acg-id.com

Document # 1507-DTS-01-0-02

Subject to technical modifications 05/06