

SmartBoard

G83-6744



Facts & Features

- Common Criteria EAL 3+ certified for electronic signatures
- Secure PIN entry (class 2 reader)
- PC/SC smart card reader
- CT-API and OCF support
- Protocols:
T=0, T=1, S=8, S=9 and S=10
- EMV 2000 Terminal level 1 approved
- CCID-compatible
- Compliant with ISO 7816
- Individual and easy key assignment due to our KeyM@n Software with new, comfort functions

Delivery Volume

- 1 SmartBoard keyboard
- 1 manual
- 1 driver

Approvals

- CE, BG-GS, GS, FCC, UL, c-tick, GOST-R, VCCI, USB 2.0
- EMV 2000 level 1
- Microsoft Windows™ 2000, XP, Vista

Operating systems

- Windows 98, ME, 2000, XP, XP 64Bit, Vista, CE, Linux, Mac OS X

System requirements

- USB interface

Technical Data

- Number of keys:
104 = US Layout with Windows™ keys
105 = EU Layout with Windows™ keys
- Weight:
approx. 1250 g (without packaging)
approx. 1500 g (with packaging)
- Dimensions:
approx. 458 x 195 x 54 mm (keyboard)
approx. 493 x 255 x 58 mm (packaging)
- Cable length:
approx. 1.75 m
- Storage temperature:
-20 °C until 60 °C
- Operating temperature:
0 °C until 50 °C
- Operating life of single keys:
20 million operations
- Insertion cycles:
approx. 100,000 operations (sliding contacts)
approx. 200,000 operations (landing contacts on request)
- Smart Card Speed:
412,903 bps
- Smart Card clock:
4,8 MHz
- Interface:
USB, full speed
- Current consumption:
max. 100 mA
- Packaging unit:
40 keyboards per master carton
80 keyboards per pallet
- Guarantee period:
2 years

Order description

<i>Order number</i>	<i>Housing colour</i>	<i>Others</i>
G83-6744LUAXX-0	light grey	-
G83-6744LUAXX-2	black	-
G83-6744LUZXX-0	light grey	certified
G83-6744LUZXX-2	black	certified

Country versions:

BE	Belgium
CH	Switzerland
DE	Germany
ES	Spain
EU	US-English with €-symbol
FR	France
GB	UK-English
HU	Hungary
IT	Italy
PO	Poland
RG	US-English/cyrillic
SF	Sweden / Finland
TS	Czech Republic

(Other country versions upon request.)

Applications you will see at http://www.cherry.de/english/partners/partners_solution.htm

Cherry GmbH
Cherrystraße
91275 Auerbach/Opf.
Germany

Phone: +49 9643 18-0
Internet: www.cherry.de
www.cherrycorp.com

Sales: +49 1805 243779 (01805-Cherry)
E-Mail: sales@cherry.de
Fax: +49 9643 18-1545

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice.
Technical data relates to product specifications only.
Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2007 Cherry GmbH, Last update: 05.10.2007_V10