

# SmartReader

## SR-4044



### Facts & Features

- PCMCIA interface for integration into notebooks
- Corresponds to all current standards
- PC/SC smart card reader
- CT-API and OCF support
- EMV 2000 terminal level 1 approved

### Delivery volume

- 1 SmartReader

### Approvals

- WHQL (Microsoft)
- EMV 2000
- UL

### Operating systems

- Windows 98, ME, 2000, XP, XP 64Bit, CE, Linux, Mac OS X

### System requirements

- PCMCIA interface

### Technical data

- Protocols:  
T=0, T=1  
I<sup>2</sup>C (S=8)  
2-wire SLE4432/42 (S=10)  
3-wire SLE4418/28 (S=9)
- Smart Card Speed:  
up to 412,903 bps
- Dimensions:  
85 x 54 x 5 mm
- Weight:  
60 g
- Insertion cycles:  
approx. 100,000 operations
- Operating temperature:  
10 °C to 55 °C
- Smart Card clock:  
up to 8 MHz
- Interface:  
PCMCIA with 16 Mbps
- Current consumption:  
max. 60 mA
- Guarantee period:  
2 years

## Order description

<i>Order number</i>	<i>Colour</i>	<i>Interface</i>	<i>EAN-Code</i>
SR-4044	silver	PCMCIA	4025112057946

Cherry GmbH  
Cherrystraße  
91275 Auerbach/Opf.  
Germany

Phone: +49 9643 18-0  
Internet: [www.cherry.de](http://www.cherry.de)  
[www.cherrycorp.com](http://www.cherrycorp.com)

Sales: +49 1805 243779 (01805-Cherry)  
E-Mail: [sales@cherry.de](mailto:sales@cherry.de)  
Fax: +49 9643 18-1545

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice. Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2008 Cherry GmbH, Last update: 17.01.08\_V07

