

# Advanced Performance Line ST-1000 Smartcard Reader USB



## Key benefits

- High-quality PC/SC smart card reader with USB connection
- Card Man 2020-compatible
- "One-hand operation" possible due to heavy weight and stable base

## Delivery volume

Smart card reader  
Printed manual  
CD-ROM

## Approvals

VDE, GS, cRUus, CE, FCC  
Microsoft WHQL Windows™ ME, 2000, XP

## Technical Data

### Host Interface:

USB

### Smart Card Interface:

Reads and writes all ISO 7816 cards  
supports T=0, T=1, I<sup>2</sup>C (S=8), 2 wire (S=10),  
3 wire (S=9)

### Drivers:

PC/SC, CT-API

### Operating Systems:

Windows 98, ME, NT 4, 2000, XP, CE  
Linux, MacOS X

### Cable length:

approx. 1.75 m

### Power consumption:

max. 100 mA

### Card connecting unit

approx. 100,000 insertions  
sliding contacts  
landing contacts on request

### Weight:

approx. 300 g (without packaging)  
approx. 350 g (with packaging)

### Dimensions:

approx. 75 x 51 x 55 mm (smart card reader)  
approx. 60 x 195 x 60 mm (packaging)

### Packaging unit:

64 readers per box  
384 per pallet

### Storage temperature:

-20 °C until 60 °C

### Operating temperature:

0 °C until 50 °C

### Guarantee period:

2 years

### Order description

Order number	Housing (top)	Housing (base)
ST-1000 UB	light grey	black

Cherry GmbH  
Cherrystraße  
D-91275 Auerbach/Opf.  
Phone: +49 (0) 9643 18-0  
Hotline: +49 (0) 9643 18-206  
Fax: +49 (0) 9643 18-1545  
Internet: [www.cherry.de](http://www.cherry.de)

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice. Technical data relate to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2004 Cherry GmbH