

Smart Terminal

ST-1044U



Facts & Features

- High-quality smart card reader with USB interface
- Card Man 3212 compatible
- "One-hand operation" with high weight and stable stand
- PC/SC smart card reader
- CT-API and OCF support
- T=0, T=1, S=8, S=9 and S=10 protocols
- CCID compatible
- EMV 2000 terminal Level 1-approved
- USB 2.0 compatible

Delivery volume

- 1 Smart Terminal
- 1 manual
- 1 CD-Rom

Approvals

- VDE, GS, cRUus, CE, FCC, VCCI
- Microsoft WHQL Windows™ 2000, XP, Vista
- EMV 2000 Level 1

System requirements

- USB interface

Operating systems

- Windows 98, ME, 2000, XP, XP 64Bit, Vista, Vista 64, CE, Linux, Mac OS X

Technical data

- Smart Card interface:
 - Reads and writes all ISO 7816 cards
 - Supports T=0, T=1, I²C (S=8), 2-wire (S=10), 3-wire (S=9)
- Drivers:
CCID, PC/SC, CT-API
- Card connecting unit:
approx. 100,000 insertions sliding contacts
approx. 200,000 insertions landing contacts (upon request)
- Smart Card speed:
412,903 bps
- Clock frequency smartcard:
4.8 MHz
- Weight:
approx. 300 g (Smart Terminal)
approx. 350 g (with packaging)
- Dimensions:
approx. 75 x 51 x 55 mm (Smart Terminal)
approx. 60 x 195 x 60 mm (with packaging)
- Cable length:
approx. 1,75 m
- Current consumption:
max. 100 mA
- Interface:
USB
- Storage temperature:
-20 °C until 50 °C
- Operating temperature:
0 °C until 60 °C
- Packaging unit:
64 reader per master carton
6 master cartons per pallet
- Guarantee period:
2 years

Order description

<i>Order number</i>	<i>Housing colour</i>	<i>Packaging</i>	<i>Connecting unit</i>
ST-1044UB	light grey / black	bulk	sliding contacts
ST-1044UB-R	light grey / black	retail	sliding contacts
ST-1044UD	light grey / black	bulk	landing contacts

Applications you will see at
http://www.cherry.de/english/partners/partners_solution.htm

Cherry GmbH
Cherrystraße
91275 Auerbach/Opf.
Germany

Phone: +49 9643 18-0
Internet: www.cherry.de
www.cherrycorp.com

Sales: +49 1805 243779 (01805-Cherry)
E-Mail: sales@cherry.de
Fax: +49 9643 18-1545

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice. Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2007 Cherry GmbH, Last update: 19.11.2007_V11

