

SCR3310

The Premier USB Smart Card Reader Solution



Overview

The SCR3310 continues the line of SCM Microsystems' market-leading smart card reader products.

The SCR3310 includes support for USB and all relevant security standards; the interface is CCID and PC/SC as well as EMV2000 Level 1 compliant. The EMV certification recommends the reader especially for applications with banking or credit cards.

Together, these features enable high performance, cost effective programs for secure logical access in any environment.

SCR3310 Benefits

- On-board flash for seamless firmware upgrades - prevents obsolescence
- EMV 2000 Level 1 and PC/SC certification in a single solution
- High communication speed performance
- Fully tested and compliant with all ISO 7816 smart cards in the market
- Fully tested and compliant with all major memory smart cards in the market
- Customizing options: case, colors, and company logo

PC Security Solutions

U.S. Headquarters
 SCM Microsystems Inc.
 41740 Christy Street
 Fremont, CA 94538 USA
 E-mail scmsales@scmmicro.com
 Phone +1 510 360 2300
 Fax +1 510 360 0211

European Headquarters
 SCM Microsystems GmbH
 Oskar-Messter-Str. 13
 85737 Ismaning, Germany
 E-mail sales@scmmicro.de
 Phone +49 89 9595 5000
 Fax +49 89 9595 5555

SCM Microsystems Japan, Inc.
 8F Hirakawacho Ronstate, 2-11-1,
 Hirakawa-cho, Chiyoda-ku,
 Tokyo, Japan 102-0093
 E-mail sales@scmmicro.co.jp
 Phone +81 3 3511 8511
 Fax +81 3 3511 8516

SCM Microsystems India Pvt. Ltd.
 Module No. 0506, 0507 & 0508
 D' Block South, 5th Floor
 Tidel Park, 4 Canal Bank Road
 Taramani
 Chennai 600113, India
 E-mail sales@scmmicro.co.in
 Phone +91 44 2254 0020
 Fax +91 44 2254 0029



SCR3310

Technical Data

| | |
|-----------------------|---|
| Host Interface | <ul style="list-style-type: none"> • Full speed USB (12 Mbps) • Bus powered device • CCID compliant |
| Smart Card Interface | <ul style="list-style-type: none"> • T=0, T=1 protocol support • Memory card support through SCM MCARD API • Communication speed up to 344 kbps (PPS, FI parameter) • Frequency up to 8 MHz (PPS, DI parameter) • Support ISO 7816 Class A and AB smart card |
| Smart Card Connector | <ul style="list-style-type: none"> • 8 contacts - ISO location • 100,000 insertions • Sliding contact |
| Human Interface | <ul style="list-style-type: none"> • One dual state green LED |
| Cable/Power | <ul style="list-style-type: none"> • Cable: 1.5m long with USB type A connector • Power through USB bus |
| Dimensions | <ul style="list-style-type: none"> • LWH 70 x 70 x 10 mm, weight 60 grams |
| Operating Temperature | <ul style="list-style-type: none"> • 0° to 50° Celsius |
| OS | <ul style="list-style-type: none"> • Windows® 98, ME, 2000, XP, Server2003, Vista • Windows® CE 4.2, 5.0 • MacOS, Linux, Solaris |
| API | <ul style="list-style-type: none"> • PC/SC • CT-API (thru wrapper on top of PC/SC) |
| Approvals | <ul style="list-style-type: none"> • FCC Class B part 15, cULus, CE, VCCI • USB • Microsoft® WHQL 2000, XP, Server2003 • EMV 2000 Level 1 |
| Environmental | <ul style="list-style-type: none"> • RoHS • WEEE |

Technical data are subject to change without notice.

The SCM Microsystems' Advantage

SCM Microsystems brings over a decade of experience in ASIC and smart card reader development to this unique product. With its dedicated Research and Development team and a true global presence, SCM Microsystems delivers high quality products catering to the various requirements in the security field. SCM offers customization of products to suit application needs.

Typical advantages of an SCM Microsystems product include:

- More than 50 patents
- High quality mass production capability
- Industry endorsed SmartOS™ middleware
- Support for all current and emerging international standards
- Customer base of global, top tier PC OEMs, systems integrators and smart card industry leaders
- Direct significant long-term relationships with all leading smart card manufacturers and application providers

