

SCR333

USB Device Bay



Overview

The SCR333 is a USB smart card reader designed for integration into PCs. It can be easily integrated into every standard 3.5 inches bay. The SCR333 is based on SCM's STC II controller chip that supports multiple interfaces, multiple reader devices and all relevant security standards. The STC II chip was the industry's first to offer On-board Flash, allowing future firmware and application enhancements. These features provide SCM Microsystems with the unique ability to offer high performance and cost effective solutions.

SCR333 Benefits

- On-board flash provides seamless firmware upgrades in the field
- High performance
- Fully tested and compliant with all major smart cards in the market
- Customizing options: casing, colors, and company logo

PC Security Solutions

U.S. Headquarters
 SCM Microsystems Inc.
 41740 Christy Street
 Fremont, CA 94538 USA
 E-mail scmsales@scmmicro.com
 Phone +1 510 360 2300
 Fax +1 510 360 0211

European Headquarters
 SCM Microsystems GmbH
 Oskar-Messter-Str. 13
 85737 Ismaning, Germany
 E-mail sales@scmmicro.de
 Phone +49 89 9595 5000
 Fax +49 89 9595 5555

SCM Microsystems Japan, Inc.
 8F Hirakawacho Ronstate, 2-11-1,
 Hirakawa-cho, Chiyoda-ku,
 Tokyo, Japan 102-0093
 E-mail sales@scmmicro.co.jp
 Phone +81 3 3511 8511
 Fax +81 3 3511 8516

SCM Microsystems India Pvt. Ltd.
 Module No. 0506, 0507 & 0508
 D' Block South, 5th Floor
 Tidel Park, 4 Canal Bank Road
 Taramani
 Chennai 600113, India
 E-mail sales@scmmicro.co.in
 Phone +91 44 2254 0020
 Fax +91 44 2254 0029



SCR333

Technical Data

Host Interface	<ul style="list-style-type: none"> • Full speed USB (12 Mbps) • Bus powered device • CCID compliant
Smart Card Interface	<ul style="list-style-type: none"> • T=0, T=1 protocol support • Memory card support through SCM MCARD API • Communication speed up to 344,105 bps (PPS, FI parameter) • Frequency up to 8 MHz (PPS, DI parameter) • Support ISO 7816 Class A and AB smart card
Smart Card Connector	<ul style="list-style-type: none"> • 8 contacts - ISO location • 100,000 insertions • Sliding contact
Human Interface	<ul style="list-style-type: none"> • One dual state LED
Cable/Power	<ul style="list-style-type: none"> • 2.45mm (.100") Pitch, Single row, 5 pins connector • Power supply through USB bus
Dimensions	<ul style="list-style-type: none"> • 3.5 inches device bay, weight 70 grams
Operating Temperature	<ul style="list-style-type: none"> • 0° to 50° Celsius
OS	<ul style="list-style-type: none"> • Windows® 98, ME, 2000 and XP, Server 2003, Vista • Windows® CE 4.2, 5.0 • MacOS, Linux, Solaris
API	<ul style="list-style-type: none"> • PC/SC • CT-API (thru wrapper on top of PC/SC)
Approvals	<ul style="list-style-type: none"> • FCC Class B part 15, CE, VCCI • USB • Microsoft® WHQL 2000, XP, Server 2003 • EMV Level1 upon request
Environmental	<ul style="list-style-type: none"> • RoHS • WEEE

Technical data are subject to change without notice.

The SCM Microsystems' Advantage

SCM Microsystems brings over a decade of experience in ASIC and smart card reader development to this unique product. With its dedicated Research and Development team and a true global presence, SCM Microsystems delivers high quality products catering to the various requirements in the security field. SCM offers customization of products to suit application needs.

Typical advantages of an SCM Microsystems product include:

- More than 50 patents
- High quality mass production capability
- Industry endorsed SmartOS™ middleware
- Support for all current and emerging international standards
- Customer base of global, top tier PC OEMs, systems integrators and smart card industry leaders
- Direct significant long-term relationships with all leading smart card manufacturers and application providers

