## ingenico

# AXIUM DX8000

Smart payment and commerce solution for in-store performance



- Fresh business opportunities with leadingedge Android apps under Android 10
- Top-level security with Android & PCI PTS V6 compliancy
- Supported by AXIUM platform to unlock the full potential of digital commerce





### Based on Android 10, the AXIUM DX8000 offers a bestin-class digital experience in-store while optimizing performance, productivity and security.

#### The power of Android 10.

Harness the power of the Appstore.

#### Powerful processing to increase speed and output

- Boosted memory (Up to 3GB RAM 32GB FLASH)
- High speed processor (ARM Quad-core cortex A53)

Large, up to 6" touchscreen and ergonomic interface

#### Payment anywhere and anytime (4G, 3G, GPRS, Bluetooth and WiFi)

#### **Powerful cameras**

- Front camera (up to 2MP)
- Rear camera (up to 8MP)

Long-lasting battery for the lengthy working day (up to 3350mAh, 24.12Wh)

#### Fast integrated printer

All methods of payment accepted (EMV Chip & PIN, contactless, magstripe or digital wallets and QR-code based payment)

Raising the bar on security with PCI PTS v6



			AXIUM DX8000-5	AXIUM DX8000-2
OS	Android	Android 10 Security OS	~	~
Memory	<ul><li>Internal</li><li>External</li></ul>	<ul> <li>32GB Flash 3GB RAM</li> <li>16GB Flash,2GB RAM</li> <li>8GB Flash, 1GB RAM</li> <li>MicroSD Card slot</li> </ul>	Option V N/A V	N/A N/A ~
Processor	<ul><li> Application processor</li><li> Crypto processor</li></ul>	<ul> <li>Cortex Quad-core A53, 1.3GHz</li> <li>Security core SC300, 192MHz</li> </ul>	<b>~</b>	× ×
Card readers	<ul> <li>Magnetic card reader</li> <li>Smart card reader</li> <li>NFC/contactless</li> </ul>	<ul> <li>Support ISO 1/2/3 track data, bi-directional swiping</li> <li>EMV Contactless L1 3.0 spec compliant; support ISO / IEC 14443 Type A / B, Felica</li> </ul>	> > >	× × ×
SAM /SIM slots	• 4 slots (SAM + SIM)	<ul> <li>2 SIM + 2 SAM</li> <li>1 SIM + 3 SAM</li> </ul>	✓ Option	✓ Option
Display	Color / capacitive     multi-touch	<ul> <li>6"HD+, 1440 x 720 px</li> <li>5.5"HD, 1280 x 720 px</li> </ul>	√ N∕A	N/A ✓
Printer	<ul> <li>Integrated thermal printer</li> </ul>	Diameter: 40mm	~	~
Keys & Keypad	<ul> <li>Power key &amp; volumes keys</li> <li>Capacitive screen keys</li> </ul>	<ul> <li>1 Power key &amp; 2 volumes keys</li> <li>Virtual screen keys: Menu, Home, Back</li> <li>Physical screen keys: Menu, Home, Back</li> </ul>	✓ ✓ N/A	✓ N/A ✓
Terminal wake-up	Wake-up gesture	<ul> <li>Double click capacitive screen to wake up the terminal system</li> </ul>	~	~

		<ul> <li>Fleet management &amp; security solutions</li> <li>Hardware services</li> <li>Professional services</li> </ul>			
			AXIUM DX8000-5	AXIUM DX8000-2	
Audio	<ul><li>Support audio play</li><li>Headphone</li></ul>	<ul> <li>Support audio play</li> <li>USB C</li> </ul>	~	~	
Connectivity	• WAN	4G fallback 3G and	~	~	
	• LAN	GPRS <ul> <li>Bluetooth 4.2 support</li> <li>BLE</li> </ul>	~	~	
		• WiFi IEEE8.2.11 a/b/g/n/ ac 2.4G and 5G	~	Option	
		• WiFi IEEE8.2.11 b/g/n 2.4G only	N/A	~	
Connections	• USB	• USB Type C	~	~	
Data capture	Positionning	<ul> <li>Tracking GPS, GLON/ ASS, BEIDOU</li> </ul>	~	~	
	Rear camera	<ul> <li>8MP, autofocus, flash, code scanning</li> </ul>	Option	N/A	
		<ul> <li>5MP, autofocus, flash, code scanning</li> </ul>	~	~	
	Front camera	<ul> <li>2MP, fixed focus camera, code scanning</li> </ul>	~	N/A	
		<ul> <li>0.3MP, fixed focus camera, code scanning</li> </ul>	N/A	~	
Battery	• Li-ion	<ul> <li>3350mAh / 7.2V, 24.12Wh</li> <li>2600mAh / 7.2V, 18.7Wh</li> </ul>	N/A	N/A	
Size	Terminal only	<ul> <li>198 x 83 x 62.5 mm (7.79 x 3.26 x 2.46")</li> </ul>	~	~	
Weight	• Terminal + battery	• 450g (15.87oz)	~	~	
Security	PCI PTS V6		~	~	
Environment	<ul> <li>Operating Temperature</li> </ul>	<ul> <li>-10°C to +50°C (14°F to 122°F)</li> </ul>	~	~	
	Storage     Temperature	<ul> <li>-20°C to +70°C (-4°F to 158°F)</li> </ul>	~	~	
	<ul> <li>Operating</li> </ul>	<ul> <li>10% to 90%</li> <li>non-condensing</li> </ul>	~	~	

Diagnostic List

Smartcard

Camera

Wif

Magnetic Card

ingenico

AXIUM DX8000

un nom

۳

3(11)

6

